

Data Sheet



RWB

Mounting Base for Main Powered Smoke Alarm - Wireless Interconnect For use with R240 & R240RC

Key Information

Product brand
Product or component
Device application
Colour
Quantity per set
Type of packing

Red Smoke Alarms Mounting Base Mounting White (RAL 9003) Set of 1 Carton

Complementary

[US] rated supply voltage	220240 V AC
[le] rated operational current	40mA maximum
Battery Type	Sealed rechargeable
Battery life 10 Year	
Transmission Frequency	433.92 MHz
Number of device	Interconnect 40pcs smoke alarm (wired or
	wireless interconnected)
Operating Distance	30m indoor use line of sight
	100m in free field
Remote control type	Only with wireless remote control switch with
	max 30m
Time delay range	2 min for pairing
Connections - Terminals	For live: Screw terminal with 2 x 15mm2 wiring capacity
	For neutral: Screw terminal with 2 x 1.5 mm ² wiring capacity
	For earth loop: Screw terminal with 2 x 15mm² wiring capacity
	For interconnect: Screw terminal with 2 x 15mm² wiring capacity
Local Signally	1 red LED flashing once every 10s for low battery
Type of installation	Indoor
Diameter	140 mm
Height	55 mm

Environment

Ambient air temperature t	for operation	045°C
Relative humidity		595%
Standards		AS 4268

It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein

Neither Red Smoke Alarms PTY. LTD nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

specific application or use thereof.



Data Sheet R240 It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant

Neither Red Smoke Alarms PTY. LTD nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability of reliability of these products for specific user applications.

Authorised Distributor

EvacuLife.com.au

1300 994 890

